


Coil

Grades: 304, 304L, 316L

Finishes: 2B, BA, No. 4

Unit of Supply: Kg

Certification: Acc. to ASTM A240/A480



CSS

Product Code	Grade	Finish	Product Size (mm)	Description	kg/m
G304 - 2B					
CSS055G3042B+0915	G304	2B	0.55mm x 0915	COIL G304 2B ASTM A240/A480	4.02
CSS055G3042B+1219	G304	2B	0.55mm x 1219	COIL G304 2B ASTM A240/A480	5.36
CSS090G3042B+1219	G304	2B	0.90mm x 1219	COIL G304 2B ASTM A240/A480	8.78
CSS120G3042B+1219	G304	2B	1.20mm x 1219	COIL G304 2B ASTM A240/A480	11.70
CSS200G3042B+1219	G304	2B	2.00mm x 1219	COIL G304L 2B ASTM A240/A480	19.50
CSS250G3042B+1219	G304	2B	2.50mm x 1219	COIL G304L 2B ASTM A240/A480	24.38
CSS300G3042B+1219	G304	2B	3.00mm x 1219	COIL G304L 2B ASTM A240/A480	29.25
CSS090G3042BP+1219	G304	2B LPE	0.90mm x 1219	COIL G304 2B LPE ASTM A240/A480	8.78
CSS090G3042BP+1500	G304	2B LPE	0.90mm x 1500	COIL G304 2B LPE ASTM A240/A480	10.80
CSS120G3042BP+0915	G304	2B LPE	1.20mm x 0915	COIL G304 2B LPE ASTM A240/A480	8.78
CSS120G3042BP+1219	G304	2B LPE	1.20mm x 1219	COIL G304 2B LPE ASTM A240/A480	11.70
CSS120G3042BP+1500	G304	2B LPE	1.20mm x 1500	COIL G304 2B LPE ASTM A240/A480	14.40
CSS120G3042BP+1524	G304	2B LPE	1.20mm x 1524	COIL G304 2B LPE ASTM A240/A480	14.63
CSS150G3042BP+1219	G304	2B LPE	1.50mm x 1219	COIL G304 2B LPE ASTM A240/A480	14.63
CSS150G3042BP+1500	G304	2B LPE	1.50mm x 1500	COIL G304 2B LPE ASTM A240/A480	18.00
CSS200G3042BP+1219	G304L	2B LPE	2.00mm x 1219	COIL G304L 2B LPE ASTM A240/A480	19.50
CSS200G3042BP+1500	G304L	2B LPE	2.00mm x 1500	COIL G304L 2B LPE ASTM A240/A480	24.00
CSS200G304L2BP+2000	G304L	2B LPE	2.00mm x 2000	COIL G304L 2B LPE ASTM A240/A480	32.00
CSS250G3042BP+1219	G304L	2B LPE	2.50mm x 1219	COIL G304L 2B LPE ASTM A240/A480	24.38
CSS250G3042BP+1500	G304L	2B LPE	2.50mm x 1500	COIL G304L 2B LPE ASTM A240/A480	30.00
CSS250G304L2BP+2000	G304L	2B LPE	2.50mm x 2000	COIL G304L 2B LPE ASTM A240/A480	40.00
CSS300G3042BP+1219	G304L	2B LPE	3.00mm x 1219	COIL G304L 2B LPE ASTM A240/A480	29.25
CSS300G3042BP+1500	G304L	2B LPE	3.00mm x 1500	COIL G304L 2B LPE ASTM A240/A480	36.00
CSS300G304L2BP+2000	G304L	2B LPE	3.00mm x 2000	COIL G304L 2B LPE ASTM A240/A480	48.00
CSS400G304L2BP+1500	G304L	2B LPE	4.00mm x 1500	COIL G304L 2B LPE ASTM A240/A480	48.00
CSS400G304L2BP+2000	G304L	2B LPE	4.00mm x 2000	COIL G304L 2B LPE ASTM A240/A480	64.00
G304 - BA					
CSS120G304BA+0915	G304	BA LPE	1.20mm x 0915	COIL G304 BA LPE ASTM A240/A480	8.78
CSS120G304BA+1219	G304	BA LPE	1.20mm x 1219	COIL G304 BA LPE ASTM A240/A480	11.70
G304 - No. 4					
CSS120G304NO4+0915	G304	NO4 LPE	1.20mm x 0915	COIL G304 NO4 LPE ASTM A240/A480	8.78
CSS120G304NO4+1219	G304	NO4 LPE	1.20mm x 1219	COIL G304 NO4 LPE ASTM A240/A480	11.70
CSS120G304NO4+1524	G304	NO4 LPE	1.20mm x 1524	COIL G304 NO4 LPE ASTM A240/A480	14.63
CSS150G304NO4+0915	G304	NO4 LPE	1.50mm x 0915	COIL G304 NO4 LPE ASTM A240/A480	10.98
CSS150G304NO4+1219	G304	NO4 LPE	1.50mm x 1219	COIL G304 NO4 LPE ASTM A240/A480	14.63

Coil processing up to 3mm is available in New Zealand
Laser cutting quality film standard (100 microns)

Other grades and sizes available on request ex. mill stock or production.


Coil

Grades: 304, 304L, 316L

Finishes: 2B, BA, No. 4

Unit of Supply: Kg

Certification: Acc. to ASTM A240/A480



CSS

Product Code	Grade	Finish	Product Size (mm)	Description	kg/m
G316L - 2B					
CSS200G316L2BP+1219	G316L	2B LPE	2.00mm x 1219	COIL G316L 2B LPE ASTM A240/A480	19.50
CSS200G316L2BP+1500	G316L	2B LPE	2.00mm x 1500	COIL G316L 2B LPE ASTM A240/A480	24.00
CSS250G316L2BP+1219	G316L	2B LPE	2.50mm x 1219	COIL G316L 2B LPE ASTM A240/A480	24.38
CSS250G316L2BP+1500	G316L	2B LPE	2.50mm x 1500	COIL G316L 2B LPE ASTM A240/A480	30.00
CSS300G316L2BP+1219	G316L	2B	3.00mm x 1219	COIL G316L 2B ASTM A240/A480	29.25
CSS300G316L2BP+1219	G316L	2B LPE	3.00mm x 1219	COIL G316L 2B LPE ASTM A240/A480	29.25
CSS300G316L2BP+1500	G316L	2B LPE	3.00mm x 1500	COIL G316L 2B LPE ASTM A240/A480	36.00
CSS400G316L2BP+1500	G316L	2B LPE	4.00mm x 1500	COIL G316L 2B LPE ASTM A240/A480	48.00

Cut-to-length options available in New Zealand or offshore.

Coil processing up to 3mm is available in New Zealand
Laser cutting quality film standard (100 microns)

Other grades and sizes available on request ex. mill stock or production.