

Seamless Hydraulic Tube

Types: Sandvik 3R60 / ASTM 316L with 2.5% min. Molybdenum (W 1.4435)

Grades: 316L

Unit of Supply: 6m lengths

Finishes: Bright Annealed (up to 30mm), sizes larger than 30 mm O.D. are in the annealed and pickled condition

Certification: Acc. to ASTM A269/A213



HTSH

Product Code	Product Size (mm)	Description	Weight ea (kg)	kg/m
HTSH006010G316L+0600	6.00 x 1.00mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	0.75	0.13
HTSH008015G316L+0600	8.00 x 1.50mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	1.46	0.24
HTSH010010G316L+0600	10.00 x 1.00mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	1.35	0.23
HTSH010015G316L+0600	10.00 x 1.50mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	1.91	0.32
HTSH012015G316L+0600	12.00 x 1.50mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	2.36	0.39
HTSH012020G316L+0600	12.00 x 2.00mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	3.00	0.50
HTSH014020G316L+0600	14.00 x 2.00mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	3.60	0.60
HTSH015015G316L+0600	15.00 x 1.50mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	3.04	0.51
HTSH016020G316L+0600	16.00 x 2.00mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	4.20	0.70
HTSH018020G316L+0600	18.00 x 2.00mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	4.80	0.80
HTSH020025G316L+0600	20.00 x 2.50mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	6.56	1.09
HTSH022020G316L+0600	22.00 x 2.00mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	6.00	1.00
HTSH025030G316L+0600	25.00 x 3.00mm	HYDRAULIC TUBE G316L BA - A269/A213 MIN MOLY 2.5%	9.90	1.65
HTSH028020G316L+0600	28.00 x 2.00mm	HYDRAULIC TUBE G316L A & P- A269/A213	7.80	1.30
HTSH030030G316L+0600	30.00 x 3.00mm	HYDRAULIC TUBE G316L A & P- A269/A213	12.15	2.03
HTSH038030G316L+0600	38.00 x 3.00mm	HYDRAULIC TUBE G316L A & P- A269/A213	15.76	2.63